

RETRIEVABLE BRIDGE PLUG V-ZERO™



FEATURES

- Qualified for all sizes from 2 3/8" to 7.00"
- High performance monobore design
- Set at any depth in tubing or casing
- Adaptable for multiple well applications
- Set using conventional intervention setting tools, such as Omega's Hydrostatic Setting Tool (HST).
- Option to install a Lower Junk Catcher Extension in high debris environments

APPLICATIONS

- Well barrier during well maintenance and workover's.
- Zonal isolation, water shut off or treatment.
- Pre-installation in completion tail-pipe for packer setting.
- Contingency packer setting.
- Testing of production tubing(s)

BENEFITS

- Increased operational performance due to setting and releasing mechanisms.
- No specialized retrieval tool required, standard GS pulling tool used to equalise and retrieve.
- Optimised slip design reduces stress loading on tubulars.
- Controlled setting action, further enhanced with the Omega HST.
- Through bore design provides secondary functionality and increased debris tolerance



More Information please contact :

Bala : 012 522 2484/nurbaizura@neudimension.com.my

PERMANENT DOWNHOLE GAUGE



FUNCTIONS

- High Pressure High Temperature Gauges (High Temperature Up to 600°F. High Pressure Up to 30,000 psi)
- Industry's Most Reliable Sensor (Longevity, High Accuracy & Best Resolution)
- Multiple Communication Port
- Shock & Vibration Resistance
- 98% Reliability
- Intelligent Well Interface Standardization compliant for subsea applications (IWIS)



More Information please contact :

Bala : 012 522 2484/nurbaizura@neudimension.com.my